

# MATERIAL SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** ..... PRO-SET® LAM-224  
**PRODUCT CODE:** ..... LAM-224  
**CHEMICAL FAMILY:** ..... Amine  
**CHEMICAL NAME:** ..... Modified polyamine  
**FORMULA:** ..... Not applicable

**MANUFACTURER:**  
Gougeon Brothers, Inc.  
100 Patterson Avenue  
Bay City, MI 48706, U.S.A.  
Phone: 888-377-6738 or 989-684-7286  
[www.prosetepoxy.com](http://www.prosetepoxy.com)

**EMERGENCY TELEPHONE NUMBERS:**  
Transportation  
CHEMTREC: ..... 800-424-9300 (U.S.)  
703-527-3887 (International)  
Non-transportation  
Poison Hotline: ..... 800-222-1222

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**HMIS Hazard Rating:**    **Health - 3**                      **Flammability - 1**                      **Physical Hazards - 0**

DANGER Toxic by inhalation. Causes burns to eyes and skin. Harmful if swallowed. Harmful in contact with skin. Possible reproductive hazard. Can cause allergic reactions. Harmful if released to the environment. Amber colored liquid with ammonia odor.

**PRIMARY ROUTE(S) OF ENTRY:** ..... Skin and eye contact, inhalation.

### POTENTIAL HEALTH EFFECTS:

**ACUTE INHALATION:** ..... Toxic. Exposure to vapor or mist is irritating to the upper respiratory tract, causing nasal discharge, coughing, and discomfort in eyes, nose, throat and chest. Severe cases may cause difficult breathing and lung tissue damage.

**CHRONIC INHALATION:** ..... May cause lung damage. May cause respiratory sensitization in susceptible individuals. Repeated exposures may cause internal organ damage.

**ACUTE SKIN CONTACT:** ..... Corrosive. Prolonged contact may cause skin damage with burns and blistering. Wide spread contact may result in material being absorbed in harmful amounts.

**CHRONIC SKIN CONTACT:** ..... May cause persistent irritation or dermatitis. Repeated contact may cause allergic reaction/sensitization and possible tissue destruction. Can be absorbed through the skin in amounts that can cause internal organ damage.

**EYE CONTACT:** ..... Corrosive. May cause blurred vision. May cause irritation with corneal injury resulting in permanent vision impairment or even blindness.

**INGESTION:** ..... Corrosive. May cause gastrointestinal irritation or ulceration. May cause burns of the mouth and throat. Aspiration hazard.

**SYMPTOMS OF OVEREXPOSURE:** ..... Skin irritation, burns and blistering. Irritation of the nose and throat, possible headache. Eye irritation and blurred vision. Can cause liver and kidney damage.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** ..... Existing respiratory conditions, such as asthma and bronchitis. Existing skin conditions.

## 3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

<u>INGREDIENT NAME</u>	<u>CAS #</u>	<u>CONCENTRATION (%)</u>
Aminoethylpiperazine	141-31-8	10-30
Benzene-1,3-dimethanamine	1477-55-0	10-30
Paratertiarybutylphenol	98-54-4	10-20
Trimethylhexamethylenediamine	25620-58-0	10-20
Trade Secret	NA	10-20
1,3-Propandiamine, N,N'-1,2-ethandiylbis-	10563-26-5	0-10

Nonylphenol

25154-52-3

0-5

**4. FIRST AID MEASURES**

**FIRST AID FOR EYES:**.....Immediately flush with water for at least 15 minutes. Get prompt medical attention.

**FIRST AID FOR SKIN:**.....Remove contaminated clothing. Immediately wash skin with soap and water. Do not apply greases or ointments. Get medical attention if severe exposure.

**FIRST AID FOR INHALATION:**.....Move to fresh air and consult physician if effects occur.

**FIRST AID FOR INGESTION:**.....Do not induce vomiting. Rinse mouth with water. Prevent aspiration hazard. If vomiting should occur spontaneously, keep airway clear. Get medical attention.

**5. FIRE FIGHTING MEASURES**

**FLASH POINT:** .....> 200°F (Open Cup)

**EXTINGUISHING MEDIA:**.....Dry chemical, alcohol foam, carbon dioxide (CO<sub>2</sub>), dry sand, limestone powder.

**FIRE AND EXPLOSION HAZARDS:**.....Burning can generate toxic fumes. Products of combustion may include, but not limited to: oxides of nitrogen, volatile amines, ammonia, nitric acid, nitrosamines. When mixed with sawdust, wood chips, or other cellulosic material, spontaneous combustion can occur under certain conditions. If hardener is spilled into or mixed with sawdust, heat is generated as the air oxidizes the amine. If the heat is not dissipated quickly enough, it can ignite the sawdust.

**SPECIAL FIRE FIGHTING PROCEDURES:**.....Use full-body protective gear and a self-contained breathing apparatus. Use of water may generate toxic aqueous solutions. Do not allow water run-off from fighting fire to enter drains or other water courses.

**6. ACCIDENTAL RELEASE MEASURES**

**SPILL OR LEAK PROCEDURES:**.....Stop leak without additional risk. Wear proper personal protective equipment. Dike and contain spill. Ventilate area. Large spill - dike and pump into appropriate container for recovery. Small spill - recover or use inert, non-combustible absorbent material (e.g., sand, clay) and shovel into suitable container. Do not use sawdust, wood chips or other cellulosic materials to absorb the spill, as the possibility for spontaneous combustion exists. Wash spill residue with warm, soapy water if necessary.

**7. HANDLING AND STORAGE**

**STORAGE TEMPERATURE (min./max.):** .....40°F (4°C) / 90°F (32°C).

**STORAGE:**.....Store in cool, dry place with adequate ventilation.

**HANDLING PRECAUTIONS:**.....Use only with adequate ventilation. Do not breath vapors or mists from heated material. Avoid contact with skin and eyes. Wash thoroughly after handling. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**EYE PROTECTION GUIDELINES:**.....Chemical splash goggles, full-face shield or full-face respirator.

**SKIN PROTECTION GUIDELINES:**.....Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

**RESPIRATORY/VENTILATION GUIDELINES:**.....General mechanical or local exhaust ventilation. With inadequate ventilation, use a NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or a supplied-air respirator.

**ADDITIONAL PROTECTIVE MEASURES:**.....Use where there is immediate access to safety shower and emergency eye wash. Provide proper wash/cleanup facilities for proper hygiene. Contact lens should not be worn when working with this material. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the potential for harmful exposure to this product under normal use conditions.

**OCCUPATIONAL EXPOSURE LIMITS:**.....Not established for product as whole. Refer to OSHA's Permissible Exposure Level (PEL) or the ACGIH Guidelines for information on specific ingredients.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL FORM**.....Liquid.  
**COLOR**.....Clear.  
**ODOR**.....Ammonia-like.  
**BOILING POINT**.....> 480°F.  
**MELTING POINT/FREEZE POINT**.....No data.  
**pH**.....11.4  
**SOLUBILITY IN WATER**.....Appreciable.  
**SPECIFIC GRAVITY**.....1.00  
**BULK DENSITY**.....8.38 (pounds/gallon.)  
**VAPOR PRESSURE**.....< 1 mmHg @ 20°C.  
**VAPOR DENSITY**.....Heavier than air.  
**VISCOSITY**.....75 (cP)  
**% VOLATILE BY WEIGHT**.....ASTM 2369-07 was used to determine the Volatile Matter Content of mixed epoxy resin and hardener.

Resin/Hardener	VOC Content	
	(g/L)	(lb/gal)
LAM-125 / LAM-224	3.60	0.03
LAM-135 / LAM-224	1.66	0.01
LAM-145 / LAM-224	1.13	0.01

**10. STABILITY AND REACTIVITY**

**STABILITY:**.....Stable.  
**HAZARDOUS POLYMERIZATION:** .....Will not occur.  
**INCOMPATIBILITIES:**.....May react violently when in contact with oxidizing materials, acids or halogenated compounds such as methylene chloride. Reactions may be slow initially, then may rapidly generate heat and vapor pressure.  
**DECOMPOSITION PRODUCTS:**.....Very toxic fumes and gases when burned or otherwise heated to thermal decomposition. Decomposition products may include, but not limited to: oxides of nitrogen, volatile amines, ammonia, nitric acid.

**11. TOXICOLOGICAL INFORMATION**

No specific oral, inhalation or dermal toxicology data is known for this product.  
 Oral: ..... Expected to be moderately toxic.  
 Inhalation:..... Expected to be moderately toxic.  
 Dermal:..... Expected to be moderately toxic.  
**CARCINOGENICITY:**  
 NTP ..... No.  
 IARC..... No.  
 OSHA ..... No.  
 No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA, NTP or IARC.

**12. ECOLOGICAL INFORMATION**

Harmful if released to the environment. Toxic to aquatic organisms. This product is not readily biodegradable. May present long term environmental hazards. Do not allow into sewers, on the ground or in any body of water.

**13. DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:**.....Evaluation of this product using RCRA criteria shows that it is not a hazardous waste, either by listing or characteristics, in its purchased form. It is the responsibility of the user to determine proper disposal methods.  
 Incinerate, recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

**14. TRANSPORTATION INFORMATION**

**DOT**

D.O.T. SHIPPING NAME: ..... Polyamines, liquid, corrosive, n.o.s.  
 TECHNICAL SHIPPING NAME: ..... Benzene-1,3-dimethanamine.  
 D.O.T. HAZARD CLASS: ..... Class 8  
 U.N./N.A. NUMBER: ..... UN 2735  
 PACKING GROUP: ..... PG II

**IATA**

SHIPPING NAME: ..... Polyamines, liquid, corrosive, n.o.s.  
 TECHNICAL SHIPPING NAME: ..... Benzene-1,3-dimethanamine  
 HAZARD CLASS: ..... Class 8  
 U.N. NUMBER: ..... UN 2735  
 PACKING GROUP: ..... PG II  
 MARINE POLLUTANT: ..... Yes

**IMDG**

SHIPPING NAME: ..... Polyamines, liquid, corrosive, n.o.s.  
 TECHNICAL SHIPPING NAME: ..... Benzene-1,3-dimethanamine  
 HAZARD CLASS: ..... Class 8  
 U.N. NUMBER: ..... UN 2735  
 PACKING GROUP: ..... PG II  
 MARINE POLLUTANT: ..... Yes

**15. REGULATORY INFORMATION**

**OSHA STATUS:** ..... Corrosive; toxic by inhalation; target organ effects; possible sensitizer.

**WHMIS STATUS:** ..... D1B, D2B, E

**TSCA STATUS:** ..... All components are listed on TSCA inventory or otherwise comply with TSCA requirements.

**SARA TITLE III:**

**SECTION 313 TOXIC CHEMICALS:** ..... None.

**STATE REGULATORY INFORMATION:**

The following chemicals are specifically listed or otherwise regulated by individual states. For details on your regulatory requirements you should contact the appropriate agency in your state.

<b><u>COMPONENT NAME</u></b>	<b><u>STATE CODE</u></b>
Benzene-1,3-dimethanamine	NJ, PA, MA
Paratertiarybutylphenol	PA, NJ
Nonylphenol	NJ, PA, MA

**16. OTHER INFORMATION**

**REASON FOR ISSUE:** ..... New product.  
**PREPARED BY:** ..... G. M. House  
**APPROVED BY:** ..... G. M. House  
**TITLE:** ..... Health, Safety & Environmental Manager  
**APPROVAL DATE:** ..... October 25, 2012  
**SUPERSEDES DATE:** ..... NA  
**MSDS NUMBER:** ..... XH12-172-80B-12a

Note: The Hazardous Material Indexing System (HMIS), cited in the Emergency Overview of Section 3, uses the following index to assess hazard rating: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; and 4 = Severe.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gougeon Brothers, Inc. The data on this sheet is related only to the specific material designated herein. Gougeon Brothers, Inc. assumes no legal responsibility for use or reliance upon these data.